JD200-5

Intelligent Pressure And Sanitary Transmitter





Main Features

Accuracy : ±0,075% **Output Signal** : 4 to 20 mA

Communication Protocol : Hart

: 9 ~32 Vcc, without polarity – 12 mA **Power Supply**

Work Temperature : -20 to 100 °C

: Linear and Square Root **Output Types**

Protection : IP66 : 50 ms **Response Time** Rangeability Thermal Stability

: ±0,15% URL, 5 years Display : With backlight

Configuration

: Hart Config (free software) or Pushbuttons

Sanitary Flange Connection : Tri Clamp, SMS, IDF, RJT

Sanitary Flange Diaphragm : Stainless Steel, Hastelloy, Monel, Tantalum

Special Diaphragm Coating : Hallar, Tefzel

Sanitary Flange Filling Oil : DC704, DC200, Neobee



JD200-5

ORDER CODE





200-S : Intelligent Pressure And Sanitary Transmitter COMMUNICATION PROTOCOL														
•		H : 4 to 20 mA Hart												
٠					05									
•	•		BRATIO											
•	•	2	: 0 to 5000 mmH2O											
•	•	3	: 0 to 25000 mmH2O											
•		4	: 0 to 25 Kgf / cm ² DIAPHRAGM MATERIAL / FILLING OIL 1 : Stainless Steel / Silicone Oil CAPACITIVE SENSOR MATERIAL											
•		•												
		•												
•	•	•												
•		•		: Stainless Steel										
•		•		•		IELL MATERIAL - ELECTRIAL CONNECTION								
				•	Α		: Aluminium - 1/2 NPT Thread							
				•		SANIT	ARY FL	ANGE	CONNE	CTION				
						1	: Tri-C	lamp 1	1/2" W	ithout E	xtension	В	: IDF 2" With Extension	
						2	: Tri-C	lamp 2	" With E	xtensio	on	С	: IDF 2" Without Extension	
						3	: Tri-Clamp 2" Without Extension				D	: IDF 3" With Extension		
						4	4 : Tri-Clamp 3" With Extension				Е	: IDF 3" Without Extension		
						5	: Tri-Clamp 3" Without Extension				F	: RJT 2" With Extension		
						6	6 : SMS 1 1/2" Without Extension				G	: RJT 2" Without Extension		
						7	7 : SMS 2" With Extension				Н	: RJT 3" With Extension		
						8	8 : SMS 2" Without Extension				1	: RJT 3" Without Extension		
						9	: SMS 3" With Extension				Z	: Special		
						Α	: SMS	: SMS 3" Without Extension						
							SANIT	ARY FL	ANGE	MATER	IAL			
							1	: Stain	nless Steel					
								SANIT	TARY FLANGE DIAPHRAGM MATERIAL					
								1	: Stainless Steel					
								2	: Hast	: Hastelloy				
								3	: Mone	el 400				
								4	: Tanta	: Tantalum				
								5	: Halla	: Hallar Coating				
						_		6		Tefzel Coating				
						_				NITARY FLANGE FILLING OIL				
									1		ne DC704			
									2					
						_			3	: Neobee				
						_			Z	: Special				
										PAINT				
			•					•		0	: Standard	Senso	or Br (Synthetic Liquid Paint)	
	•	•	•	•	•	•		•	•	1				
•	•	•	•	•	•	•	•	•	•	1 : Especial (Ver Notas) . VACCUM PROCESS				
•	•	•	•	•	•	•	•		•	•	0	: No		
•	•	•	•	•	•	•	•	•	•	•	1	: Yes		
•	•	•	•	•	•			•	•	•		. 165		

