



PRODUTO

JD200-SRF : Selo Remoto Flangeado

CONEXÃO AO PROCESSO

1	: 1" 150 # (ANSI B16.5)	A	: 4" 150 # (ANSI B16.5)
2	: 1" 300 # (ANSI B16.5)	B	: 4" 300 # (ANSI B16.5)
3	: 1" 600 # (ANSI B16.5)	C	: 4" 600 # (ANSI B16.5)
4	: 2" 150 # (ANSI B16.5)	D	: DN25 PN 10/40
5	: 2" 300 # (ANSI B16.5)	E	: DN40 PN 10/40
6	: 2" 600 # (ANSI B16.5)	F	: DN50 PN 10/40
7	: 3" 150 # (ANSI B16.5)	G	: DN80 PN 10/40
8	: 3" 300 # (ANSI B16.5)	H	: DN100 PN 10/16
9	: 3" 600 # (ANSI B16.5)	Z	: Especial (Ver Notas)

COMPRIMENTO DA EXTENSÃO

0	: 00 mm
1	: 50 mm
2	: 100 mm
3	: 150 mm
4	: 200 mm
Z	: Especial (Ver Notas)

MATERIAL DO FLANGE

1	: Aço Inox
---	------------

MATERIAL DO DIAFRAGMA

1	: Aço Inox
2	: Hastelloy
3	: Monel 400
4	: Tântalo
5	: Revestimento Hallar
6	: Revestimento Tefzel

FLUÍDO DE ENCHIMENTO

1	: Silicone DC704
2	: Silicone DC200
3	: Neobee
Z	: Especial (Ver Notas)

COMPRIMENTO DO CAPILAR

1	: 1 m	8	: 8 m
2	: 2 m	9	: 9 m
3	: 3 m	A	: 10 m
4	: 4 m	B	: 11 m
5	: 5 m	C	: 12 m
6	: 6 m	Z	: Especial (Ver Notas)
7	: 7 m		

USO EM VÁCUO

0	: Não
1	: Sim (Moeda Soldada)

JD200-SRF 7 0 1 1 1 2 0