



PRODUTO									
JD200-SRR	: Selo Remoto Roscado								
.	CONEXÃO AO PROCESSO								
.	1	: 1/4 NPT							
.	2	: 3/8 NPT							
.	3	: 1/2 NPT							
.	4	: 3/4 NPT							
.	5	: 1 NPT							
.	6	: 1 1/2 NPT							
.	.	MATERIAL DO FLANGE							
.	.	1	: Aço Inox						
.	.	.	MATERIAL DO DIAFRAGMA						
.	.	.	1	: Aço Inox					
.	.	.	2	: Hastelloy					
.	.	.	3	: Monel 400					
.	.	.	4	: Tântalo					
.	.	.	.	FLUÍDO DE ENCHIMENTO					
.	.	.	.	1	: Silicone DC704				
.	.	.	.	2	: Silicone DC200				
.	.	.	.	3	: Neobee				
.	.	.	.	Z	: Especial (Ver Notas)				
.	.	.	.	.	COMPRIMENTO DO CAPILAR				
.	.	.	.	.	1	: 1 m	8	: 8 m	
.	.	.	.	.	2	: 2 m	9	: 9 m	
.	.	.	.	.	3	: 3 m	A	: 10 m	
.	.	.	.	.	4	: 4 m	B	: 11 m	
.	.	.	.	.	5	: 5 m	C	: 12 m	
.	.	.	.	.	6	: 6 m	Z	: Especial (Ver Notas)	
.	.	.	.	.	7	: 7 m			
.	.	.	.	.	.	USO EM VÁCUO			
.	.	.	.	.	.	0	: Não		
.	.	.	.	.	.	1	: Sim (Moeda Soldada)		
JD200-SRR	1	1	1	1	2	0			