

JD200-T

Intelligent Temperature Transmitter



Main Features



- **Output Signal** : 4 to 20 mA
- **Communication Protocol** : Hart
- **Power Supply** : 9 ~ 32 Vcc
- **Protection** : IP66
- **Display** : With backlight
- **Configuration** : Hart Config (free software) or Pushbuttons
- **Work Temperature** : -40 to 85 °C
- **Sensor Type** : RTD, TC, Ohm, mV



SENSOR BR

www.sensorbr.com.br

JD200-T

ORDER CODE



PRODUCT					
JD200-T	: Intelligent Temperature Transmitter				
COMMUNICATION PROTOCOL					
H	: 4 to 20 mA Hart				
ELECTRICAL CONNECTION					
1	: 1/2 NPT Thread				
SENSOR TYPE					
1	: RTD - PT100	C	: Thermocouple - Type K		
2	: RTD - PT50	D	: Thermocouple - Type N		
3	: RTD - PT200	E	: Thermocouple - Type R		
4	: RTD - PT500	F	: Thermocouple - Type T		
5	: RTD - PT1000	G	: Thermocouple - Type DIN L		
6	: RTD - COBRE	H	: Thermocouple - Type U		
7	: RTD - NIQUEL (Ni120)	I	: Thermocouple - Type W5RE26		
8	: RTD - OHMS (R)	J	: Thermocouple - Type GOST L		
9	: Thermocouple - Type E	K	: Thermocouple - mV -120 to 120		
A	: Thermocouple - Type J	L	: Thermocouple - mV -1000 to 1000		
B	: Thermocouple - Type B				
MOUNTING BRACKET					
0	: Without Mounting Bracket				
1	: With Mounting Bracket - Type L				
PAINT					
0	: Standard Sensor Br (Synthetic Liquid Paint)				
1	: Special				
JD200-T	H	1	1	1	0